

<b>Product Description</b>	A classic alkyd based Universal Undercoat , which has been especially formulated to give the best long term performance for coating on a wide range of prepared house hold surfaces such as doors, window frames, down pipes etc , under Paint Master Water and Alkyd Based Top Coats	
<b>Application Areas</b>	<ul style="list-style-type: none"> <li>• Hardboard and fibre cement boards.</li> <li>• Primed metal and wooden substrates.</li> </ul>	
<b>Product Features</b>	<ul style="list-style-type: none"> <li>• A high hiding power, low gloss Finish for Interior and Exterior use</li> <li>• Excellent adhesion and hiding power., easily sanded</li> <li>• Excellent, no mess application properties.</li> <li>• Can be cleaned with normal house hold cleaners on a regular basis.</li> </ul>	
<b>Product Data</b>	<b>Resin Base</b>	Synthetic Alkyd resin
	<b>Drying Time</b>	Touch dry: 2-4 hours Hard dry: 16-18hours
	<b>Film Thickness</b>	± 30 microns
	<b>Spreading Rate</b>	6-8 SQM per 1 litre Although the spreading rate will vary with porosity and type of substrate, for uncoated new surfaces work on 7-9 square metres per litre for the first coat and 9-11 square metres per litre for subsequent coats and for when applied to sealed, previously painted substrates.
	<b>Surface Appearance</b>	Low Gloss
<b>Application Details</b>		
• <b>Mixing</b>	Always stir well before use with a flat paddle.	
• <b>Application Method</b>	<ul style="list-style-type: none"> <li>• Brush, roller or spray application.</li> </ul>	
• <b>Thinning</b>	This is ready for use un-thinned; thinning with White Spirits will reduce its hiding power.	
• <b>Cleaning</b>	Application equipment clean up is with White Spirits	
• <b>Application</b>	<ul style="list-style-type: none"> <li>• With brush, roller or spray, apply a generous coat of Paint Master Universal Undercoat to the area that needs protecting.</li> <li>• Consult Paint Master when Paint Master Universal Undercoat is used as a base for Wall Paper.</li> <li>• Allow to dry overnight before recoating.</li> <li>• Application equipment clean up is with White Spirits.</li> <li>• Do not apply before 09:00 and after 16:00 in the winter.</li> </ul>	
<b>Surface Preparation</b>		
• <b>Rusted Metal</b>	<ul style="list-style-type: none"> <li>• Remove any rust and mill scale from steel surface.</li> <li>• Affected areas need to be cleaned back to bright metal</li> <li>• Apply one coat of Solvent or Water Based Metal Red Oxide , leave to dry over and apply a coat of Paint Master Universal Undercoat, allow to dry over night lightly sand, wash off sand allow to dry .</li> <li>• Apply two coats of Paint Master High Gloss Enamel.</li> </ul>	
• <b>New Metal</b>	<ul style="list-style-type: none"> <li>• Degrease surfaces with an abrasive Degreaser to remove the manufacturer's grease protective layer. This process is repeated until the surface is water break free.</li> <li>• After drying Apply one coat of Solvent or Water Based Metal Red Oxide , leave to dry over and apply a coat of Paint Master Universal Undercoat, allow to dry over night lightly sand, wash off sand allow to dry .</li> <li>• Apply two coats of Paint Master High Gloss Enamel</li> </ul>	

<ul style="list-style-type: none"> <li>• <b>Previously Painted Surfaces</b></li> </ul>	<ul style="list-style-type: none"> <li>• Make sure old paint coatings are firm and solid.</li> <li>• Remove all loose, flaking and bubbling paint.</li> <li>• Remove all dust, grease, foreign material, fungal and algae growth.</li> <li>• If powdery or friable, seal with Paint Master Bonding Liquid.</li> <li>• Prime with Paint Master WB or SB Plaster Primer.</li> <li>• Apply a coat of Paint Master Universal Undercoat</li> <li>• Allow to dry then apply 2 Coats of Paint Master High Gloss Enamel</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Wood and Wood Fibre Boards</b></li> </ul>	<ul style="list-style-type: none"> <li>• Sand surface until smooth.</li> <li>• Apply one coat of Paint Master Universal Undercoat.</li> <li>• Apply two coats of Paint Master Gloss Enamel.</li> </ul>
<b>Colour Range and Quantities</b>	<ul style="list-style-type: none"> <li>• White</li> <li>• Available in 1 litre, 5 litres and 20 Litres.</li> </ul>
<b>Precautions</b>	<ul style="list-style-type: none"> <li>• This product is flammable.</li> <li>• Use only in well ventilated areas.</li> <li>• Do not eat, drink or smoke while applying.</li> <li>• This product contains no toxic substances.</li> </ul>
<b>Disclaimer</b>	<p>Martin Vosloo Paints can not be held liable if the product fails due to improper surface preparation or application.</p>
<b>Martin Vosloo Paints</b>	
<p>011-7083166/083-2671122</p>	<p><a href="mailto:martinvosloo@mweb.co.za">martinvosloo@mweb.co.za</a></p>